

Interlink Supply of Houston
1717 Gessner
Houston, TX 77080 USA
Phone: 713-464-1147

Safety Data Sheet

Section 1: Product and Company Information

Product Identifier

Product Name:

Product Number:

Odor Solv

n/a

24 Hour Emergency Phone Numbers:

800-535-5035

Section 2: Hazards Identification

<u>GHS Classification</u>	Flammable liquids; Category 3 Skin irritation; Category 2 Eye irritation; Category 2A Specific target organ toxicity – single exposure; Category 3 (Central nervous system) Aspiration hazard; Category 1
<u>GHS Label Elements</u>	
Signal Word:	DANGER
Symbols:	
Hazard Statements:	H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airway. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Appearance: Color Varies

Physical State: Liquid

Odor: Fragrance varies,
hydrocarbon odor

Precautionary Statements – Prevention	P240 Ground/bond container and receiving equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge.
Precautionary Statements – Response	Specific treatment (See Section 4 on SDS) IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CONTROL or doctor/physician. Collect spillage.
Precautionary Statements – Disposal	Dispose of contents/container to an approved waste disposal plant.
Hazards not otherwise classified (HNOC) Other information Unknown Acute Toxicity	0% of the mixture consists of ingredient(s) of unknown toxicity

Section 3: Composition / Information on Ingredients

Chemical Name	CAS No.	Weight-%	Trade Secret
Naphtha (petroleum), heavy alkylate	64741-65-7	0 – 100	*
Naph (pet), hydrotreated hv	64742-48-9	0 – 100	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: First Aid Measures

General Advice:	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for us or safety data sheet if possible). Symptoms of poisoning may appear several hours later. Do not leave victim unattended.
Eye Contact:	Rinse immediately with plenty of water, also under eyelids, for at least 15 minutes. After initial flushing, remove any contact lenses and continue to flush for 15 minutes. Protect unharmed eye. Keep eye wide open while rinsing. If irritation persists, consult a specialist.
Skin Contact:	Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
Inhalation:	Remove to fresh air. Consult a physician after significant exposure.
Ingestion:	Do NOT induce vomiting. Drink plenty of water. Do not give milk or alcoholic beverages. Rinse mouth. Never give anything by mouth to an unconscious person. Seek medical attention immediately.
Self-protection for first aider:	
Note to physicians:	

Section 5: Fire-Fighting Measures

Suitable Extinguishing Media:	Alcohol resistant foam, CO ₂ , Dry Chemical
Hazardous Combustion Products:	CO ₂ , Carbon Monoxide, unburned hydrocarbons
Specific Hazards Arising from Chemical:	Do not allow run-off from fire-fighting measures to enter drains or water courses.
Protective equipment and precautions for fire-fighters:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: Accidental Release Measures

Personal Precautions:	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Spill Clean-Up:	Prevent further leakage or spillage if safe to do so. Soak up with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal.

Section 7: Handling and Storage

Advice on Safe Handling:	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e. pilot lights, electric motors and static electricity). Take precautionary measure against static discharge. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe mist/spray.
Storage Conditions:	Keep tightly closed in a dry and cool place. Keep in properly labeled containers. No Smoking.
Incompatible Materials:	None known based on information supplied.

Section 8: Exposure Controls

<u>Control Parameters</u>	<u>Exposure Limits</u>
Naphtha (petroleum), heavy alkylate	OSHA TWA 500 ppm 2,000 mg/m ₃
Naph (pet), hydrotrtd hvy	OSHA TWA 500 ppm 2,000 mg/m ₃

Personal Protective Equipment	
Eye/Face Protection:	Wear safety glasses with side shields (or goggles). Wear a face shield if splashing hazard exists.
Skin and Body Protection:	Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection:	No protection equipment is needed under normal use conditions. In the case of vapor formation use a respirator with approved filter.
General Hygiene Considerations:	When using do not eat, drink or smoke. When using do not smoke. Wash hands before breaks and at the end of workday.

Section 9: Physical and Chemical Properties

Physical State:	Liquid	Color:	Clear, colorless
pH:	Not applicable	Odor:	Hydrocarbon-like
Boiling Point:	340-399°F	Vapor Pressure: MM HG/20 DEG, C:	0.8 mmHg @ 20°C
Specific Gravity:	0.842	Evaporation Rate: (Butyl Acetate = 1)	0.1
Solubility:	Insoluble in water		

Section 10: Stability and Reactivity

Chemical Stability and Reactivity	Stable under recommended storage conditions.
Possible Hazardous Reactions	None under normal processing.
Conditions to Avoid	Heat, flames and sparks.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Section 11: Toxicological Information

Acute Toxicity				
Product/Ingredient Name	Result	Species	Dose	Exposure
CAS 64741-65-7	Oral LD50	Rat	>2,000 mg/kg	-
	Dermal LD50	Rabbit	>2,000 mg/kg	-
CAS 64742-48-9	Oral LD50	Rat	>5,000 mg/kg	-
	Dermal LD50	Rabbit	>3,000 mg/kg	-
	Inhalation LC50	Rat	> 5610	-

Information on likely routes of exposure	
Product Information	Harmful by inhalation and in contact with eyes and skin.
Inhalation:	Avoid breathing vapors or mists. Inhalation of vapors or mists. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Eye Contact:	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin Contact:	Avoid contact with skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking. May cause sensitization by skin contact.
Ingestion:	Do not taste or swallow. May be harmful if swallowed.

Section 12: Ecological Information

Environmental Effects:	There is no information available at this time for this product. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.
General Notes:	

Section 13: Disposal Considerations

Waste Information:	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.
---------------------------	---

Section 14: Transport Information

Regulatory Information	UN Number	Proper Shipping Name	Classes	PG*	Label
DOT Classification	UN1268	Petroleum Distillates, n.o.s.	3	III	
IMDG Class	UN1268	Petroleum Distillates, n.o.s.	3	lii	
Special Note: The flashpoint for this material is greater than 100°F. Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.					

NOTE: DOT Classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG*: Packaging Group

Section 15: Regulatory Information

CWA (Clean Water Act)	This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act.
CERCLA	This material, as supplied does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Reauthorization Act (SARA). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Section 16: Other Information

	Health Hazards	Flammability	Physical Hazards	Personal Protection
HMIS	2	2	0	B
NFPA	2	2	0	

Issue Date: 03-15-2015

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in text.